

# Working with ease...

## Stretch Wrapping Equipment

These wrappers are efficient and highly effective at preventing back strain and injury, which are the most common of all workplace injuries (1994, Worksafe Australia) because they are designed to eliminate the dangerous and time-consuming practice of stretch wrapping by hand. As employers have become more aware of occupational health and safety, stretch wrapping by hand has become less and less viable.

### Easy Wrapper Stretch Wrapper

Easy Wrapper Manual and Semi Auto Specifications:	
Power:	240Volt
Rotation speed:	9 rpm
Load capacity:	2000kg
Shipping weight:	250/300kg
Shipping dimension:	3150/3450 long 1400 wide (with mast lowered) 750 high
Mast height:	2440/2650mm
Wrapping height:	Approx 2200/ 2600mm
Turntable height:	110mm

PEW1 Manual  
PEW2 Semi Auto



**Manual Easy Wrapper PEW1** has a motorised rotating turntable and a manually counter balanced carriage to make the manual raising and lowering of the carriage easy. The operator simply guides the carriage up and down the mast to apply the film in any pattern.

**Semi Automatic Easy Wrapper PEW2** has a powered mast carriage and all manual effort is eliminated. The operator simply attaches the film and starts the wrap cycle with the push of a button. Multiple variable wrap patterns can be selected to enclose any kind of load with loads ranging up to 2.6 metres. Film usage is decreased by the mechanical tensioning attachment and the Semi Auto Easy Wrapper is durable and designed for many years of efficient service. Stretching the film with the aid of a mechanical tensioning device reduces film usage. Semi Auto Easy Wrapper is a basic stretch wrapper with the durability of more sophisticated machines, but without many of the expensive options, priced to suit workplaces with light to moderate stretch wrapping needs.

#### FEATURES (MANUAL & SEMI AUTO)

- Fork tine sockets for easy relocation
- Large diameter chequer plate turntable
- Fold down mast for transport
- Galvanised base assembly, robust mechanism

#### OPTIONS (MANUAL & SEMI AUTO)

- Soft start or variable speed
- Three-phase motor and low-voltage controls
- Kit to allow hand rolls to be used

#### FEATURES (SEMI AUTO ONLY)

- Turntable return to start
- Software storage for up to 9-user set wrapping patterns
- Improved-tensioning system provides constant tension independent of Roll diameter

- Quick release lever to disengage tensioner
- Half, full and top sheet cycles

#### OPTIONS (SEMI AUTO ONLY)

- Height of pallet to be wrapped can be keyed in or alternatively height Sensing can be achieved using a photo-eye (optional)
- 3200mm extended mast
- **Cubing and weighing:** With this option the Semi Automatic Easy Wrapper stretch wrapper will be able to wrap, cube and weigh your pallets in the same time as wrapping only. There should be a considerable payback if there are inadvertent overcharges from freight companies.

#### Code PEW2CW

### Lo-Wrapper Stretch Wrapper

Lo-Wrapper Manual and Semi Auto Specifications:	
Power:	240Volt
Rotation speed:	9 rpm
Load capacity:	2000kg
Shipping weight:	350/400kg
Shipping dimension:	3200/3450 long 1300 wide (with mast lowered) 750 high
Mast height:	2420/2650mm
Wrapping height:	approx 2200/ 2600mm
Turntable height:	26mm

PLW1 Manual  
PLW2 Semi Auto



**Manual Lo Wrapper PLW1** is a low profile stretch wrapper that features a turntable height of only 26mm. This allows an operator to use either a hand pallet truck or a forklift to place or remove pallets from the wrapper when a forklift is not always readily available for this task, especially in smaller operations. It has a motorised rotating turntable and a manually counter balanced carriage to make the manual raising and lowering of the carriage easy. The operator simply guides the carriage up and down the mast to apply the film in any pattern.

**Semi Automatic Lo Wrapper PLW2** has a powered mast carriage and all manual effort is eliminated. The operator simply attaches the film and starts the wrap cycle with the push of a button. Multiple variable wrap patterns can be selected to enclose any kind of load with loads ranging up to 2.6 metres. Film usage is decreased by the mechanical tensioning attachment and the Semi Auto Lo Wrapper is durable and designed for many years of efficient service. Stretching the film with the aid of a mechanical tensioning device reduces film usage. Lo-Wrapper is priced to suit workplaces with light to moderate stretch wrapping needs.

#### FEATURES (SEMI AUTO ONLY)

- Turntable return to start
- Software storage for up to 9-user set wrapping patterns
- Half, full and top sheet cycles
- Improved-tensioning system provides constant tension independent of roll diameter
- Quick release lever to disengage tensioner

can be achieved using a photo-eye (optional).

- 3200mm extended mast

#### OPTIONS (MANUAL AND SEMI AUTO)

- Soft start or variable speed
- Additional ramps (one is supplied standard)
- Relocation frame for easy relocation of the Lo-wrapper
- Three-phase motor and low-voltage controls
- Kit to allow hand rolls to be used

#### OPTIONS (SEMI AUTO ONLY)

- Height of pallet to be wrapped can be keyed in or alternatively height sensing

This Australian manufactured, blown stretch wrap film, is available in natural or black. The black is used to deter possible theft of expensive products working on the principle "if they don't know what it is there is less reason to take it". All rolls are 500mm wide & have a 76mm core diameter. There are 50 rolls per pallet.

### Machine Stretch Wrap Film

Code	Length m x thickness	Colour
P1527	1800 x 17um	Natural
P1523	1800 x 20um	Natural
P1530	1500 x 23um	Natural
P1535	1500 x 25um	Natural
P1432	1800 x 20um	Black
P1433	1500 x 25um	Black