

# BATTERY STORAGE CABINET SPECIFICATIONS

- Double walled sheet steel construction with a 40mm thermic air barrier
- High capacity liquid tight sump to contain spills - 150mm deep
- Self-closing, close fitting doors held shut by catches at 2 points. The doors do not open inwards and are capable of being opened from within the cabinet
- Built in flash arrestors and vent openings [for mechanical ventilation systems]
- Strong fully adjustable shelving perforated for free air movement, 100mm adjustment increments
- Sequential door closing system
- Stainless steel pin with continuous hinging for strength and reliability
- State of the art powder coat finish for high durability and performance
- Distinct safety signs and directions that comply with AS 1216 and AS 1319
- Designed and Manufactured in full conformance to AS/ NZS 4681:2000 The storage and handling of Class 9 (miscellaneous) dangerous goods and articles



## SC160BS Specification

Dimensions (mm)			
	H	W	D
External	1220	1100	450
Internal	973	1018	370

Shelf Levels	2
Max Capacity	160L
Sump Capacity	56L
Weight (kg)	78.0 kg

Australia Wide Sales & Service

sales@materialshandling.com.au | www.materialshandling.com.au | 1300 65 00 35

**MATERIALS**  
**Handling** *Working with ease*  
PTY LTD