

LOAD LEVELLING DEVICES

Pro Series



L5 Pro

Levelling and turning when lifting

- Auto levelling
- Load capacity: Max. 5 tons
- Load imbalance capacity: Max. 750 kg
- Unloaded weight: 139 kg
- Standard chain length: 3 meters
- Release of chain wheel with remote control.
- Flash light warning when chain wheel is released.
- Auto levelling, finds the center of gravity automatically when chain wheel is released.
- Snatch block function with released chain wheel.



L5 Pro plus

Upcoming model
Levelling and turning when lifting

- Memory function
- Auto levelling
- Load capacity: Max. 5 tons
- Load imbalance capacity: Max. 750 kg
- Unloaded weight: 139 kg
- Standard chain length: 3 meters
- Release of chain wheel with remote control.
- Flash light warning when chain wheel is released.
- Auto levelling, finds the center of gravity automatically when chain wheel is released.
- Snatch block function with released chain wheel.



L12 Pro

Levelling and turning when lifting

- Auto levelling
- Load capacity: Max. 12 tons
- Load imbalance capacity: Max. 2500 kg
- Unloaded weight: 295 kg
- Standard chain length: 4 meters
- Release of chain wheel with remote control.
- Flash light warning when chain wheel is released.
- Auto levelling, finds the center of gravity automatically when chain wheel is released.
- Snatch block function with released chain wheel.



L20-3 Pro

Levelling and turning when lifting

- Auto levelling
- Load capacity: Max. 20 tons
- Load imbalance capacity: Max. 3 tons
- Unloaded weight: 395 kg
- Standard chain length: 6 meters
- Release of chain wheel with remote control.
- Flash light warning when chain wheel is released.
- Auto levelling, finds the center of gravity automatically when chain wheel is released.
- Snatch block function with released chain wheel.

Australia Wide Sales & Service

sales@materialshandling.com.au | www.materialshandling.com.au | 1300 65 00 35

MATERIALS
Handling *Working with ease*
PTY LTD

Heavy Duty Series

Levelling Devices



L10 Heavy Duty

Levelling and turning when lifting

- Load capacity: Max. 10 tons
- Load imbalance capacity: Max. 4 tons
- Unloaded weight: 260 kg
- Standard chain length: 3 meters



L50 Heavy Duty

Upcoming model, sales start Q2 Levelling and turning when lifting

- Load capacity: Max. 50 tons
- Load imbalance capacity: Max. 15 tons
- Unloaded weight: 1150 kg
- Standard chain length: 6 meters

Basic Series

Levelling Devices



L3

Levelling and turning when lifting

- Load capacity: Max. 3 tons
- Load imbalance capacity: Max. 500 kg
- Unloaded weight: 126 kg
- Standard chain length: 3 meters

The only maintenance required, aside from cleaning, is charging the battery. The battery status is indicated on the levelling device and, with normal use, it is sufficient to charge the battery once a week.