

MANUAL PUSH TROLLEYS KITO TSP SERIES



Applications

- ✓ Mining, construction, engineering, infrastructure, manufacturing
- ✓ Ideal for processing plants, manufacturing plants, job sites, construction sites, projects

Features

- ✓ Push or pull, no electricity required.
- ✓ For curved beams where tight turns are required, Kito's TSP trolleys allow a low minimum turn radius.
- ✓ Engineered to be lighter and easier to install, the 250kg to 5 tonne model TSP trolleys are specifically designed to be robust and durable, without unnecessary weight and bulkiness.
- ✓ TSP Trolley wheels are adjustable to work with both tapered and flat-flanged beams, allowing you to use existing equipment without customization.
- ✓ Lifetime-lubricated ball bearings also increase reliability and provide you with smooth operation while traversing a load.
- ✓ Japanese bearings used on wheels.
- ✓ Available with different connectors for use with different products.

The reliability, operational smoothness and safety of your hoist depends on the trolley. Heat-treated steel wheels, sealed bearings and a low-turn radius are just some of the benefits of a push trolley from Kito.


Capacity: 250kg – 5T



KITO TSP Series Manual Push Trolleys





TSP
for ER2 electric chain hoist
with connector E




TSP075-100

*For informational purposes only, contact KITO for dimensional drawing; Please Specify H or I beam when ordering 7.5t and up, by placing an "I" or "H" behind the part number.



TSP001-050

*For informational purposes only, contact KITO for dimensional drawing



Dimensions

Capacity	Model	a	b	c	d	e	f	j	h	i	g	k	heightroom (mm)
250kg	TSP003	204	102	182	84	20	60	76	22	b-45	23	89	
500kg	TSP005	204	102	182	84	20	60	76	22	b-45	23	89	
1 tonne	TSP010	249	127	236	112	29	71	95	25	b-48	25	114	
1.5 tonne	TSP015	300	153	280	131	35	85	112	32	b-57	33	163	
2 tonne	TSP020	300	153	280	131	35	85	112	32	b-57	33	163	
2.5 tonne	TSP025	320	153	324	152	36	100	134	36	b-62	39	188	
3 tonne	TSP030	320	153	324	152	36	100	134	36	b-62	39	188	
5 tonne	TSP050	297	178	400	178	46	118	144	54	b-77	58	229	

Specifications

Part No.	Capacity	Model	Standard Flange (mm)					Min. Radius for Curve (mm)	Net Weight (kgs)
			Standard	W20 Extension	W20 Extension Kit Part No.	W30 Extension	W30 Extension Kit Part No.		
47507	250kg	TSP003	50-102	103-203	---	204-305	---	1100	4.5
47508	500kg	TSP005	50-102	103-203	47493	204-305	47494	1100	4.5
47509	1T	TSP010	58-127	128-203	47438	154-305	47439	1300	8
47510	1.5T	TSP015	82-153	---	---	154-305	47440	1500	14
47511	2T	TSP020	82-153	---	---	154-305	47440	1500	14
47512	2.5T	TSP025	82-153	---	---	154-305	47495	1700	23
47513	3T	TSP030	82-153	---	---	154-305	47495	1700	23
47514	5T	TSP030	100-178	---	---	179-305	47496	2300	50