

STAINLESS STEEL SCISSOR LIFT TABLES

Platform, base frame and scissors are made of stainless steel AISI 304/1.4301, the surface is glass blasted. Shafts, wheels and bolts AISI 303/1.4305. Fittings and tubes are electro galvanised, and safety frame made of aluminum. The power unit is covered by a stainless plate.

Return pipe(s) from cylinder(s) to tank, with the exception of the super low models, TR 500 and TRD 500 as there is no room for it.

Cylinder type 1: Standard coating, incl. standard fittings (electro galvanised).

Cylinder type 2: With special coating. Piston rod and joint bed are in stainless steel. Piston tube sandblasted, primed and painted twice with 2-component polyurethane paint, incl. standard fittings (electro galvanised).

Cylinder type 3: With AISI 316/1.4401 tube. Piston rod AISI 329/1.4460 and joint bed AISI 420/1.4031. Incl. stainless steel fitting AISI316/1.4401.

Type/Capacity kg	Travel mm	Closed height mm	Total raised height mm	Length mm	Width mm	Lift time sec	Motor kW	Weight kg
Single scissor								
TR 500 *	550	160	710	900	650	11	0,37	115
TL 1000	830	180	1010	1300	650	18	0,75	160
TL 1000 B	830	180	1010	1300	800	18	0,75	175
TL 1000 F	830	180	1010	1300	1000	18	0,75	180
TL 2000 ⌘	820	230	1050	1300	800	27	0,75	240
TL 2000 F ⌘	820	230	1050	1300	1000	27	0,75	250
TM 1500	1100	230	1330	1700	900	27	0,75	315
TM 1500 B	1100	230	1330	1700	1200	27	0,75	365
TS 2000	1500	250	1750	2200	1200	35	2,2	580
TS 2000 B	1500	250	1750	2200	1500	35	2,2	650
Double scissor								
TRD 500 *	1100	270	1370	900	650	18	0,37	140
TLD 1000	1600	375	1975	1300	800	30	0,75	310
TLD 1000 F	1600	375	1975	1300	1000	30	0,75	340
TLD 2000	1600	400	2000	1300	900	32	2,2	375
TMD 1000	2150	400	2550	1700	900	41	2,2	500
TMD 2000	2150	400	2550	1700	900	59	2,2	605
Superlow, excl. ramp								
TCB 1000	715	85	800	1500	800	12	0,75	260
TCB 1000 F	715	85	800	1500	1000	12	0,75	275
TCB 1500	715	85	800	1500	800	15	1,1	300
TCB 1500 F	715	85	800	1500	1000	15	1,1	345
TCB 2000	695	105	800	1500	800	16	1,1	340
TCB 2000 F	695	105	800	1500	1000	16	1,1	360

Ramp for TCB

TCB 1000/1500 (F), L x W: 600x800 mm

TCB 2000, L x W: 800x800 mm



Additional price

Separate power unit (standard on superlow tables) covered by a stainless plate. Recommended as it facilitates cleaning

Hydraulic fittings made from Stainless steel (optional: by Cylinder TYPE 1 and 2).

Stainless steel safety trip bar

TR-, TL-, TB-, TM- and the TCB models

TA Models and beyond TUB Models

*There is no cover over the power unit, as there is no room for it.

€ The collapsed height is higher compared to the painted models.

Australia Wide Sales & Service

sales@materialshandling.com.au | www.materialshandling.com.au | 1300 65 00 35

MATERIALS
Handling PTY LTD *Working with ease.*