

# BENCH TOP BAND SEALERS SPECIFICATIONS

## The affordable bulk bag sealing solution

With one compact machine you can set up your own packaging line. Simply feed the filled bags in at one end and they come out the other with their tops sealed.

Seals LDPE, PE, PP, PVC, cello and layered barrier bags. For bags best sealed in the vertical position such as confectionery, liquids, and pasta, choose the PMP3564. For items that need to lie flat such as magazines and stationery, choose the PMP3565.

Both models come with an imprint kit for adding an expiry date, batch number or other information during the sealing process.



PMP3564  
Vertical Band Sealer

### Specifications:

- Bag length: Sealing head to outer edge of conveyor 170 mm (PMP3565); Sealing head to conveyor adjustable from 100 mm to 260 mm (PMP3564)
- Maximum seal speed: 12 m/min
- Seal Width: 6 mm to 10 mm
- Conveyor table width: 150 mm
- Temperature range: 30°C to 300°C
- Seal distance: Below bag top adjustable from 0 to 30 mm
- Maximum seal thickness: 2 x 0.4 mm (PE)
- Belting loading capacity: Less than 6 kg
- Power consumption: 550 w
- Weight: 29 kg

### Features of PMP3564:

- Conveyor On/Off
- Seal cooling fan On/Off
- Sealing temperature control
- Sealing temperature indicator
- Conveyor speed control
- Emergency stop
- Directional options (left to right or right to left operation - specify at purchase)
- Vertical band sealer

### Features of PMP3565:

- Safety guard
- Teflon belt tension
- Seal width control
- Sealing pressure control
- Guide belt tension
- Conveyor height adjustment
- Conveyor alignment and tension adjustment
- Directional options (left to right or right to left operation - specify at purchase)
- Horizontal band sealer

Imprint Kit  
Now with photo eye  
activated thermal  
ribbon black imprinter  
PMP35652



PMP3565  
Horizontal Band Sealer

Australia Wide Sales & Service

sales@materialshandling.com.au | www.materialshandling.com.au | 1300 25 84 07

**MATERIALS**  
**Handling** *Working with ease.*  
PTY LTD