

Corrosion Proof Ladders MFNF48

Technical Data Sheet

Product Code	MFNF48
Phone Number	1300 25 84 07
Email	sales@materialshandling.com.au

PROPERTIES

✓ Standards	AS/NZS 1892.3
⚠ Load Rating	150kg
⚡ Electrical Properties	Complies to AS/NZS 1892.3 Section 2.4
🔥 Heat Resistance	130 Degrees Celsius
🧴 Chemical Resistance	Tested to AS/NZS 1892.3
☀ Accelerated Weathering Test	Tested to AS 2331.3.1
🛠 Warranty	3 years from date of manufacturing

MEASUREMENTS

🏋 Weight	Fly: 14.6kg / Base: 15kg
↕ Distance Between Rungs	0.305m
📏 Height	Fly: 4.905m / Base: 4.860m
📏 Height to Top Rung	4.495m
↔ Width	Fly: 0.365m / Base: 0.450m

COMPONENTS

A Stiles	Fibreglass: ISO-PE resin with e-glass fibres
B Rungs	Round: Fibreglass ISO-PE resin with e-glass fibres
C Feet	Thermoplastic Vulcanizate
D Rung Wear Strip	HD Polyethylene
E End Caps	35% GF Nylon PV 35H – Black
Rivets	Zinc Plated Low Carbon Steel

