

Corrosion Proof Step Platforms MFPS30

Product Code	MFPS30
Phone Number	1300 25 84 07
Email	sales@materialshandling.com.au

Technical Data Sheet

PROPERTIES

☑ Standards	AS/NZS 1892.3 / ANSI A 14.5-2000
⚠ Load Rating	150kg
⚡ Electrical Properties	Complies to AS/NZS 1892.3 Section 2.4
🔥 Heat Resistance	130 Degrees Celsius
🧪 Chemical Resistance	Tested to AS/NZS 1892.3
☁ Accelerated Weathering Test	Tested to AS 2331.3.1
🛡 Warranty	3 years from date of manufacturing

MEASUREMENTS

🏋️ Weight	45kg
↕ Distance Between Rungs	0.305m
◇ Open Height	3.9m
∨ Closed Height	4.08m
↗ Platform Height	3.0m
∟ Handrail Height	0.9m above platform
✂ Closed Width	0.2m
🪜 Number of Steps	10 including platform

COMPONENTS

A Stiles	Fibreglass: ISO-PE resin with e-glass fibres
B Rungs	Round: Fibreglass ISO-PE resin with e-glass fibres
C Feet	Thermoplastic Polyurethane
D Platform Deck	316 Stainless Steel
E Platform Hooks	316 Stainless Steel
F Handrail	316 Stainless Steel
G Brackets	316 Stainless Steel
H Rods and Struts	316 Stainless Steel
I Spacer	Polyethylene
J Step Plates	316 Stainless Steel
K Rear Step	316 Stainless Steel
Rivets	316 Stainless Steel
Nuts	316 Stainless Steel
Washers	316 Stainless Steel

