Indoor Dangerous Goods Storage Cabinets

Toxic Substances



Class 6 Toxic Substance Storage Cabinets





Dual Walled

Double walled sheet steel construction with a 40mm thermic air barrier.



Vent Openings Built in flash arrestors and vent openings [for mechanical ventilation systems.]



High Capacity Sump

High capacity liquid tight sump to contain spills - 150mm deep.



Self-Closing Doors



Perforated Adjustable Shelving

Strong fully adjustable shelving perforated for air movement, 100mm adjustment increments.



Complies with AS/NZS 4452:1997

Designed and manufactured in full conformance to AS/NZS 4452:1997 - The storage and handling of toxic substances.

Additional Features

- Stainless steel pin with continuous hinging for strength and reliability.
- Distinct Safety signs and directions that comply with AS 1216 and AS 1319.
- State of the art powder coat finish for high durability and performance.
- Sequential door closing system.


SAFE-I-STORE

Manufactured in Australia.

| SC0306 | | тохіс | 30L - Toxic Substance Storage Cabinet | | | | |
|--------|--|-------|--|------|--------|-------|--|
| | NO SMOKING NO IGNITION SOURCES WITHIN 3 METRES | 6 | Dimensions | | | | |
| | | | | н | W | | |
| | | | External | 800 | 500 | | |
| | | | Internal | 553 | 418 | : | |
| | | | Storage Levels | | | | |
| | | | Sump Capacity | | | | |
| | | | Weight | | | 33 | |
| | UN DITSIDRE | | Complies | With | AS/NZS | 4452: | |
| | | | Мах | 4L | 20L | 2 | |
| | | | 201 | 0 | 1 | | |

| Dimensions | | | | | |
|--------------------------------|-----|----------|--|--|--|
| | н | W D | | | |
| External | 800 | 500 450 | | | |
| Internal | 553 | 418 370 | | | |
| Storage Levels 2 | | | | | |
| Sump Capacity 23L | | | | | |
| Weight 33.0 kg | | | | | |
| Complies With AS/NZS 4452:1997 | | | | | |
| Max | 4L | 20L 205L | | | |
| 30L | 8 | 1 0 | | | |

SC0606





60L - Toxic Substance Storage Cabinet

| Dimensions | | | | | | |
|-------------------|-------|----------|------------------|--|--|--|
| | H W D | | | | | |
| External | 1065 | 500 | 450 | | | |
| Internal | 818 | 418 | 370 | | | |
| Storage Levels 2 | | | | | | |
| Sump Capacity 23L | | | | | | |
| Weight | | | 41.0 kg | | | |
| Complies \ | With | AS/NZS - | AS/NZS 4452:1997 | | | |
| Max | 4L | 20L | 205L | | | |
| 60L | 12* | 2 | 0 | | | |

*with 3 storage levels

| SC1006 | TOXIC | 100L - Toxic Substance Storage Cabinet | | | | |
|--|---------------------------|--|-------|------------------|---------|--|
| | | Dimensions | | | | |
| NO SMOKING NO IGNITION SOURCES WITHIN 3 METRES MAXMUM CAPACITY 100 LITRES | In St Su W Co | | н | W | D | |
| | | External | 800 | 920 | 615 | |
| | | Internal | 553 | 838 | 535 | |
| | | Storage Lev | vels | 2 | | |
| | | Sump Capa | acity | | 67L | |
| | | Weight | | | 65.0 kg | |
| | | Complies With | | AS/NZS 4452:1997 | | |
| | | Мах | 4L | 20L | 205L | |
| | | 100L | 16 | 4 | 0 | |



160L - Toxic Substance Storage Cabinet

| Dimensions | | | | | |
|-------------------|---------|----------|------------------|--|--|
| | н | W D | | | |
| External | 1220 | 1100 | 450 | | |
| Internal | 973 | 1018 370 | | | |
| Storage Levels 2 | | | | | |
| Sump Capacity 56L | | | | | |
| Weight | 78.0 kg | | | | |
| Complies V | Vith | AS/NZS | AS/NZS 4452:1997 | | |
| Max | 4L | 20L | 205L | | |
| 160L | 30* | 6 | 0 | | |

*with 3 storage levels

SC2506

| | Toxic 6 | 250L - Toxic Substance Storage Cabinet | | | | |
|--|------------|--|-------|------------------|----------|--|
| (JUDE) | v | Dimensions | | | | |
| NO SMORING No Ignition Sources Within 3 Metres | | | н | W | D | |
| rouc 6 | | External | 1750 | 1100 | 500 | |
| | | Internal | 1503 | 1018 | 420 | |
| A A | | Storage Le | evels | 3 | | |
| | | Sump Cap | acity | 64L | | |
| TRADEM CRACTY 28 UTES | | Weight | | | 123.0 kg | |
| RUE I STORE | | Complies \ | Nith | AS/NZS 4452:1997 | | |
| | | Max | 4L | 20L | 205L | |
| | | 250L | 50* | 9 | 0 | |
| | | | | | | |

*with 5 storage levels

Australia Wide Sales & Service sales@materialshandling.com.au | www.materialshandling.com.au | 1300 25 84 07

