QUICK-LIFT ARM QLA200i SPECIFICATIONS

QLA 200i

Intelligent lifting device which meets the highest standards of ergonomics, working environment, safety and efficiency.

Unique integrated mechanical, electric, pneumatic swivel simplifies use and minimizes maintenance.

Easy to use thanks to outstanding responsiveness, regardless of load weight.

Exceptional safety achieved using our intelligent control systems.

The best auto balance available regardless of load weight.


High reliability and low power consumption results in superior cost efficiency.



Quick-Lift Arm

QLA 200i

H2



Lifting capacity	Max 200 kg								
Working area	Max recommended working radius R1 = L1 - 300 mm Min recommended working radius R2 = See chart								
Stroke Length	2,7 meter								
Lift motor	Stepless servo-controlled asynchronous motor								
Power supply	230V, 50-60 Hz, 1-phase with ground protection, 10A								
Hinged arm	Arm profiles in Ultra High Strength Steel (UHSS). Available in 3 standard lengths; 3, 4 and 5 m								
Attachment	Floor pillar in painted steel with a standard height of 3 m. Optional pillar heights up to 5 m								
Manoeuvring	Manoeuvring is done with Binar Handling's patented control handle. Only a small force is needed to engage the up/down motion. When the operator let go of the handle, the up/down motion is immediately stopped								
End effector	End effectors are designed to fit customers need. Intelligent I/O signals are available for optimum functionality								
Options	Middle link, 200 mm for triple hinged arm. Note: The maximum working radius does not increase.								
	Pneumatic parking brake for arm. The brake function is activated via a manual push button on the control handle.								
	Middle link and pneumatic parking brake can not be combined.								

Control Handle

End Effector

reserves the right to make changes

Product	Part.no	L1	L2	L3	H1	H2	НЗ	H4	H5	Н6	Р	R1	R2
QLA 200i 3m	101105	3000	1500	470	549	50	143	462	253	455	467	2700	1300
QLA 200i 4m	101106	4000	2000	484	702	-105	159	618	344	615	534	3700	1400
QLA 200i 5m	101107	5000	2500	484	702	-105	159	618	347	618	534	4700	1600



A-A